

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) A catheter system for stent delivery to a vessel bifurcation, the vessel bifurcation having a main vessel and a branch vessel, comprising:
 - a catheter ~~having~~ extending between a distal ~~end, end and~~ and a proximal end, the catheter including a main vessel guidewire lumen that is adapted to receive a main vessel guidewire, ~~at least first and second catheter radiopaque markers positioned on the catheter;~~
 - a stent being disposed over the catheter, the stent having a side hole through a wall thereof;
 - a first catheter radiopaque marker arranged on the catheter distal of the stent;
 - a second catheter radiopaque marker arranged on the catheter proximal of the stent;
 - a third catheter radiopaque marker arranged on the catheter aligned with the side hole of the stent;
 - a side member disposed adjacent the catheter, the side member ~~having~~ extending between a free distal ~~end, end and~~ and a proximal end, the side member including ~~and~~ a branch vessel guidewire lumen that is adapted to receive a branch vessel guidewire, the side member being fixedly attached to the catheter at a location proximal the stent, the free distal end of the side member arranged extending through the side hole in the stent;
 - ~~an indicator to indicate that the distal end of the side member is advancing into a branch vessel, the indicator comprising at least first and second~~ a first side member radiopaque marker ~~markers positioned on the side member, member at the free distal end of the side member;~~
 - a second side member radiopaque marker positioned on the side member at a location spaced from the first side member radiopaque marker, wherein the second side member radiopaque marker is arranged aligned with the side hole of the stent when the free distal end of the side member extends into the branch vessel;
 - wherein the first and ~~second~~ third catheter radiopaque markers and the first and second side member radiopaque markers are juxtaposed in a first configuration, and at least one of the

first and second side member radiopaque markers is separated from the first and ~~second~~ third catheter radiopaque markers in a second configuration to indicate that the free distal end of the side member is advancing into the branch vessel, ~~and wherein the first catheter radiopaque marker is positioned adjacent the side hole of the stent; and~~

~~wherein the stent hole is substantially alignable with the branch vessel, and when the stent hole is substantially alignable with the branch vessel, the stent is disposed substantially in the main vessel prior to expansion;~~

~~wherein a distal portion of the side member is disposed within at least a portion of the stent and extends through the side hole of the stent prior to the side member advancing into the branch vessel.~~

2-6. (Canceled)

7. (Previously Presented) The catheter system of claim 1, wherein the side member comprises a flexible side sheath.

8. (Currently Amended) The catheter system of claim 1, further comprising a branch stent deployment device having a balloon, a guidewire lumen, an inflation lumen that is adapted to supply a fluid to inflate the balloon, and a branch vessel stent disposed over the balloon, wherein the branch stent deployment device is adapted to be advanced over the branch ~~stent~~ vessel guidewire.

9-10. (Canceled)

11. (Original) The catheter system of claim 1, further comprising a balloon disposed at the distal end of the side member.

12. (Original) The catheter system of claim 1, wherein the distal end of the side member is tapered.

13. (Original) The catheter system of claim 1, wherein the distal end of the side member is fabricated from a fluoroscopically visible material.

14. (Previously Presented) The catheter system of claim 1, wherein the catheter and the side member are fabricated from pebax and graphite.

15. (Currently Amended) The ~~catheter~~-catheter system of claim 1, further comprising a branch stent positioned on the side member.

16. (Previously Presented) The catheter system of claim 1, wherein the catheter further includes a balloon inflation lumen, and further comprising a proximal end hub having a main vessel guidewire channel that is coupled to the main vessel guidewire lumen, a branch vessel guidewire channel that is coupled to the branch vessel guidewire lumen, and a balloon inflation port that is coupled to the balloon inflation lumen.

17. (Previously Presented) The catheter system of claim 16, wherein the first and second guidewire channels are separated by about zero to 20°.

18. (Previously Presented) The catheter system of claim 1, wherein the distal end of the side member is unattached to the distal end of the catheter.

19. (Previously Presented) The catheter system of claim 18, wherein the length over which the distal end of the side member is unattached to the distal end of the catheter is approximately 2 to approximately 10 cm.

20-41. (Canceled)

42. (Currently Amended) The catheter system of claim 1, wherein the side member is fixedly

attached to the catheter at least one location is at or near the proximal end of the catheter.

43. (Currently Amended) The catheter system of claim 42, wherein the side member is fixedly attached to the catheter at least one location is along a length from the proximal end of the catheter to a location proximal to the stent.

44. (Currently Amended) The catheter system of claim 1, wherein the side member is fixedly attached to the catheter at least one a location that is spaced a distance from and is proximal to the stent.

45. (Previously Presented) The catheter system of claim 1, further comprising an expander disposed near the distal end of the catheter and wherein the stent is disposed over the expander such that upon expansion of the expander, the stent is configured to expand.

46. (Previously Presented) The catheter system of claim 45, wherein said expander is a balloon.

47. (Previously Presented) the catheter system of claim 1, wherein an outer diameter of the catheter is different than an outer diameter of the side member.

48. (Previously Presented) The catheter system claim 1, wherein the side member has a circular cross-section.

49. (Canceled)

50. (Currently Amended) A catheter system for stent delivery to a vessel bifurcation, the vessel bifurcation having a main vessel and a branch vessel, comprising:

a catheter having a distal end, a proximal end, and a main vessel guidewire lumen that is adapted to receive a main vessel guidewire;

a stent having a side hole through a wall thereof, the stent being disposed over the catheter, wherein the stent hole is substantially alignable with ~~the~~ a branch vessel, ~~and when the stent hole is substantially alignable with the branch vessel~~ the stent hole is disposed substantially in the main vessel prior to expansion; ~~and~~

a first catheter radiopaque marker arranged on the catheter distal of the stent;

a second catheter radiopaque marker arranged on the catheter proximal of the stent;

a third catheter radiopaque marker arranged on the catheter aligned with the side hole of the stent;

a side member disposed adjacent the catheter, the side member having a distal end, a proximal end, and a branch vessel guidewire lumen that is adapted to receive a branch vessel guidewire, the side member being integral with the catheter at a location proximal the stent, wherein the distal portion of the side member is disposed at least partially within a portion of the stent and at least partially extending through the side hole of the stent;

~~an indicator to indicate that the side member is advancing into a branch vessel including first and second catheter radiopaque markers on the catheter and first and second side member radiopaque markers on the side member;~~

a first side member radiopaque marker positioned on the side member at the distal end of the side member;

a second side member radiopaque marker positioned on the side member at a location spaced from the first side member radiopaque marker, wherein the second side member radiopaque marker is aligned with the side hole of the stent when the distal end of the side member has passed through the side hole and into the branch vessel;

~~wherein a distal portion of the side member is disposed within at least a portion of the stent and extends through the side hole of the stent, and wherein said first and second catheter radiopaque markers and said first and second side member radiopaque markers are moveable from a first configuration to a second configuration, wherein in the second configuration at least one of the side member radiopaque markers is separated from at least one of the first and second catheter radiopaque markers.~~

51. (Previously Presented) The catheter system of claim 50, wherein the side member comprises a flexible side sheath.
52. (Currently Amended) The catheter system of claim 50, further comprising a branch stent deployment device having a balloon, a guidewire lumen, an inflation lumen that is adapted to supply a fluid to inflate the balloon, and a branch vessel stent disposed over the balloon, wherein the branch stent deployment device is adapted to be advanced over the branch-stent vessel guidewire.
53. (Canceled)
54. (Previously Presented) The catheter system of claim 50, further comprising a balloon disposed at the distal end of the side member.
55. (Previously Presented) The catheter system of claim 50, wherein the distal end of the side member is tapered.
56. (Previously Presented) The catheter system of claim 50, wherein the distal end of the side member is fabricated from a fluoroscopically visible material.
57. (Previously Presented) The catheter system of claim 50, wherein the catheter and the side member are fabricated from pebax and graphite.
58. (Previously Presented) The catheter system of claim 50, further comprising a branch stent positioned on the side member.
59. (Previously Presented) The catheter system of claim 50, further comprising an expander disposed near the distal end of the catheter and wherein the stent is disposed over the expander such that upon expansion of the expander, the stent is configured to expand.

60. (Previously Presented) The catheter system of claim 59, wherein said expander is a balloon.

61. (Previously Presented) The catheter system of claim 60, wherein the catheter further includes a balloon inflation lumen, and further comprising a proximal end hub having a main vessel guidewire channel that is coupled to the main vessel guidewire lumen, a branch vessel guidewire channel that is coupled to the branch vessel guidewire lumen, and a balloon inflation port that is coupled to the balloon inflation lumen.

62. (Previously Presented) The catheter system of claim 61, wherein the first and second guidewire channels are separated by about zero to 20°.

63. (Previously Presented) The catheter system of claim 50, wherein the distal end of the side member is unattached to the distal end of the catheter.

64. (Previously Presented) The catheter system of claim 63, wherein the length over which the distal end of the side member is unattached to the distal end of the catheter is approximately 2 to approximately 10 cm.

65. (Previously Presented) The catheter system of claim 50, wherein the side member is fixedly attached to at least one location on the catheter.

66. (Previously Presented) The catheter system of claim 65, wherein the at least one location is at or near the proximal end of the catheter.

67. (Previously Presented) The catheter system of claim 65, wherein the at least one location is along a length, from the proximal end of the catheter to a location proximal to the stent.

68. (Previously Presented) The catheter system of claim 65, wherein the at least one location is spaced a distance from and is proximal to the stent.

69. (Previously Presented) The catheter system of claim 50, further comprising a connector coupled to the catheter, wherein the side member extends through the connector so as to be slidably positionable with respect to the catheter.

70. (Previously Presented) The catheter system of claim 50, wherein an outer diameter of the catheter is different than an outer diameter of the side member.

71. (Canceled)

72. (Currently Amended) A catheter system for stent delivery to a vessel bifurcation, the vessel bifurcation having a main vessel and a branch vessel, comprising:

a catheter having a distal end, a proximal end, and a main vessel guidewire lumen that is adapted to receive a main vessel guidewire, ~~at least two radiopaque markers positioned on the catheter;~~

a first stent having a side hole through a wall thereof, the first stent being disposed over the catheter, ~~wherein a first of the at least two radiopaque markers is positioned adjacent the side hole of the first stent;~~

a first catheter radiopaque marker arranged on the catheter distal of the stent;

a second catheter radiopaque marker arranged on the catheter proximal of the stent;

a third catheter radiopaque marker arranged on the catheter aligned with the side hole of the first stent;

a side member disposed adjacent and fixedly attached to at least one location on the catheter proximal the stent, the side member having a distal end, a proximal end, a branch vessel guidewire lumen that is adapted to receive a branch vessel guidewire, and at least two side radiopaque markers positioned on the side member, a first of the side radiopaque markers being spaced from a second of the side radiopaque markers, wherein the ~~at least two catheter~~

radiopaque markers positioned on the catheter and the at least two radiopaque markers positioned on the side member are juxtaposed in a first configuration; and

a branch stent deployment device having a balloon, a guidewire lumen, an inflation lumen that is adapted to supply a fluid to inflate the balloon, and a branch vessel stent disposed over the balloon, wherein the branch stent deployment device is adapted to be advanced over the branch ~~stent-vessel~~ guidewire;

wherein a distal portion of the side member is disposed within at least a portion of the first stent and extends through the side hole of the first stent.

73. (Currently Amended) A catheter system for stent delivery to a vessel bifurcation, the vessel bifurcation having a main vessel and a branch vessel, comprising:

a catheter having a distal end, a proximal end, a main vessel guidewire lumen that is adapted to receive a main vessel guidewire, and ~~first and second~~ catheter radiopaque markers positioned thereon;

a side member disposed adjacent the catheter, the side member having a distal end, a proximal end, a branch vessel guidewire lumen that is adapted to receive a branch vessel guidewire, and first and second side member radiopaque markers positioned thereon, the side member being integral with the catheter at a location proximal of the ~~first and second~~ catheter radiopaque markers;

a stent having a side hole through a wall thereof ~~the stent~~ being disposed over the catheter, wherein a first of the catheter radiopaque markers is arranged on the catheter distal of the stent, a second of the catheter radiopaque markers is arranged on the catheter proximal of the stent, and a third of the catheter radiopaque markers is arranged on the catheter aligned with the side hole of the stent; and

a branch stent deployment device having a balloon, a guidewire lumen, an inflation lumen that is adapted to supply a fluid to inflate the balloon and a branch vessel stent disposed over the balloon, wherein the branch stent deployment device is adapted to be advanced over the branch ~~stent-vessel~~ guidewire;

wherein a distal portion of the side member extends through the side hole of the stent, and

wherein said first and ~~second~~ third catheter radiopaque markers and said first and second side member radiopaque markers are juxtaposed in a first configuration and separated in a second configuration.

74. (Previously Presented) The catheter system of claim 72, wherein the side member is integral with the catheter at a location proximal of the first stent.

75. (Canceled)